



# Sigma DS4-ES1 Instant Issuance System with Embosser

## HIGHLIGHTS

### Sigma: The next generation of instant card issuance

Entrust Sigma Instant Issuance Systems are specifically designed for today's cloud environments and give you the ability to easily issue the most secure financial cards in the world.

- **Simple:** From unboxing to issuing cards to managing your printer, we made sure Sigma was the most user-friendly card issuance solution in the world
- **Secure:** Our industry-leading issuance security architecture will keep your cards and your customers' data safe and secure at each step of the issuance process
- **Smart:** Forward-thinking technology and scalability allow you to expand your card issuance program as your needs evolve

## KEY FEATURES & BENEFITS

### The world's most user-friendly financial card printer

- Intuitive printer dashboard lets you see printer status, order supplies, check cleaning status, update firmware, or contact help - all from your mobile device
- Seamless self-service lets you access how-to videos and other helpful resources by simply scanning a QR code on the LCD display
- Variable LED light ring lets you incorporate brand colors or other customization into your ambient environment
- Pre-loaded ribbon cassettes make switching ribbons easy
- Optional multi-hopper enables multiple card designs from a single printer
- Removable card cassettes make securing cardstock overnight a breeze



Single-hopper with embosser





# Sigma DS4-ES1 Instant Issuance System

## Unmatched security

- Dual-control access with security locks protects cardstock, supplies, and rejected cards, meeting Visa and Mastercard security requirements
- Cardstock is easily removable for secure overnight storage
- Secure boot protects system from malware or virus on boot-up
- Trusted Platform Module (TPM) manages the printer's own TLS/SSL certificates and keys
- Connection and data sent between Entrust Adaptive Issuance™ software and printer is encrypted
- Customer data is encrypted and is not stored in the printer after printing is complete

## Flexible, scalable, and easily integrated into your IT environment

- Issuance capabilities include:
  - Full-color or monochrome direct to-card printing
  - Magnetic stripe encoding
  - Contact or contactless smart card encoding
- Choose on-premises or cloud-hosted deployment
- Embossed text with metallic tipping foil for an elegant look
- Add multi-hopper for multiple pre-designed card feeding
- A full suite of services is available to help ensure your instant issuance program runs smoothly at every one of your branches





# Sigma DS4-ES1 Instant Issuance System

## TECHNICAL SPECIFICATIONS

### Standard Features & Supplies

Print technology	Dye sublimation / resin thermal transfer
Print capabilities	Single- or dual-sided edge-to-edge, full-color, and monochrome printing
Print resolution	<ul style="list-style-type: none"><li>• Standard mode: 300 dots per inch (dpi) (300 X 600, 300 X 1200) standard text, bar code, and graphics printing</li><li>• TrueMatch™ printing technology. Ability to conform to ICC color workflow</li></ul>
Print speed	<ul style="list-style-type: none"><li>• Single-sided color ribbon (YMCKT): up to 250 cards per hour (cph)</li><li>• Double-sided color ribbon (YMCKT-KT): up to 180 cards per hour (cph)</li><li>• Double-sided monochrome ribbon (black HQ): up to 500 cards per hour (cph)</li><li>• 60 seconds to encode mag stripe, indent, emboss, and top the card</li><li>• 64 seconds to print monochrome graphics, encode mag stripe, indent, emboss, and top the card</li><li>• 78 seconds to print color graphics, encode mag stripe, indent, emboss, and top the card</li></ul>
Card capacity	Input hopper: 125 cards (based on 0.03-in. card thickness) Output hopper: 25 cards Reject holding tray: 10 cards Front exception card slot
Card sizes	Thickness: 0.010 inches to 0.040 inches (0.25mm - 1.016mm) Dimension: ID-1, CR-79
Embossing/Indenting	<ul style="list-style-type: none"><li>• 75-character embossing/indenting wheel, financial format per ID-1 ISO 7811-3</li><li>• Single- or dual-sided</li><li>• Mastercard security characters   Helvetica® characters   OCR-A1, OCR-B1</li></ul>
Operating environment	Temperature: 60°F to 95°F (15°C to 35°C) Humidity: 20%-80% RH - non condensing
Magnetic stripe encoding	ISO 7811 three-track support (high- and low-coercivity) JIS Type II single-track option
Smart card personalization	<ul style="list-style-type: none"><li>• Contact and contactless smart card encoding for ISO 14443 A/B, ISO 15693, MIFARE®, MIFARE® DESFire® EV1/EV2</li><li>• Single-wire connectivity   Supports production of EMV® level-1 compliant card</li></ul>
Security features	<ul style="list-style-type: none"><li>• Software-activated lock to secure cardstock, supplies, and reject card hopper</li><li>• TLS/SSL encryption, supports AES-256</li><li>• Bolt-down ready</li><li>• Secure cable lock (sold separately)</li><li>• Concealed output hopper</li><li>• Password-protected cabinet</li><li>• Non-resettable card counter for auditing</li></ul>
LCD display languages	English, Spanish, German, Italian, and Japanese
Physical dimensions	<ul style="list-style-type: none"><li>• Printer: L 17.4 in x W 8.9 in x H 9.0 in / 44.2 cm x 22.6 cm x 22.9 cm</li><li>• Printer with optional multi-hopper: 23 in x 13.4 in x 16.2 in (58.4 cm x 34 cm x 41.1 cm)</li><li>• Bottom module (indenting, embossing, topping, card output): 15 in. x 27.5 in. x 10.5 in. (38.1 cm x 69.9 cm x 36.8 cm)</li></ul>



# Sigma DS4-ES1 Instant Issuance System

Weight	Printer: 12.1 lbs (5.49 kg) Printer with multi-hopper: 30.9 lbs (14.02 kg)
Connectivity	Ethernet
Driver operating system support	<ul style="list-style-type: none"> <li>• Windows 11</li> <li>• Windows 10 version 1909 - 64-bit - enterprise, home, professional</li> <li>• Windows 10 - 32 bit - professional or enterprise</li> </ul>
Warranties	36 months

## Optional Features & Supplies

Multi-hopper	Six-compartment hopper, 125-card capacity each (750 cards total)	
Color ribbons	YMCKT	500 images
	YMCKT-KT	350 images
	KTT	750 images
	YMCKL-KT	300 images
	ST-KT	500 images
	GT-KT	500 images
Monochrome ribbons	Black, blue, red, green, silver matte, gold matte, silver metallic, and gold metallic: 1,500 images	

Color ribbon guide: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Topcoat, S=Silver matte, G=Gold matte



Multi-hopper with embosser

Learn more at [entrust.com](https://www.entrust.com)



Global Headquarters  
 1187 Park Place, Minneapolis, MN 55379  
 U.S. Toll-Free Phone: 888 690 2424  
 International Phone: +1 952 933 1223  
[info@entrust.com](mailto:info@entrust.com) [entrust.com/contact](https://www.entrust.com/contact)

Entrust, Sigma, and the hexagon logo are trademarks, and/or service marks of Entrust Corporation in the U.S. and/or other countries. All other brand or product names are the property of their respective owners. Because we are continuously improving our products and services, Entrust Corporation reserves the right to change specifications without prior notice. Entrust is an equal opportunity employer. ©2022 Entrust Corporation. All rights reserved.  
 DS23Q2-Sigma-DS4-ES1-Instant-Issuance-System-with-Embosser-DS